

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name:	VELLWAX	
Product Uses:	Decorative Polishing paste wax for plaster & stucco	
Recommended Use:	Decorative interior paint	
Manufacturer:	Paintsmore Marketing Sdn Bhd 72A, Jalan JED 4, Bandar Parklands, 41200 Klang, Selangor, Malaysia Tel: +603-33199949 Email: info@macoavell.com	
Distributed By:	Plastern Inc P.O. Box 20643 Floral Park, New York 11002 Tel: 1-888-877-2128 Email: info@plastern.com	
Emergency Number:	North America: 1-888-877-2128	Malaysia: +603-3319 9949

SECTION 2 - HAZARD(S) IDENTIFICATION

Classification
Symbol (s) of Product



Irritant



Health Hazards

Signal Word
WARNING

GHS HAZARD STATEMENTS

Carcinogenicity, category 2 H351 Suspected of causing cancer.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P281 Use personal protective equipment as required.

P308+P313 IF exposed or concerned: Get medical advice/attention.

2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in Directives 67/548/EEC and 1999/45/EC (and subsequent amendments and supplements). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

2.2. Label elements.

Hazard labelling pursuant to Directives 67/548/EEC and 1999/45/EC and subsequent amendments and supplements.

Warning symbols: None.

Hazard sentences (R): None.

S 2 KEEP OUT OF THE REACH OF CHILDREN.

S43 IN CASE OF FIRE USE SAND, CARBON DIOXIDE OR FIRE POWDER. NEVER USE WATER.

S46 IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.

2.3. Other hazards.

Information not available.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**3.1. Substances.**

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
WATER			
CAS. 7732-18-5	50 - 60		
EC. 231-791-2			
INDEX. -			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
CAS. -	24 - 29	R10, R66, R67, Xn R65	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066 EC. 919-857-5
INDEX. -			
Reg. no. 01-2119463258-33			
BEESWAX			
CAS. 64742-43-4	14 - 19		
EC. -			
INDEX. -			
POLYSILOXANES			
CAS. 63148-62-9	3 - 3,5		
EC. -			
INDEX. -			

STEARIN

CAS. 57-11-4

2,5 - 3

Xi R36/37/38

Eye Irrit. 2 H319, Skin Irrit. 2 H315,
STOT SE 3 H335

EC. 200-313-4

INDEX. -

DIETHANOLAMINE

CAS. 111-42-2

1 - 1,5

Xn R22, Xn R48/22, Xi R38, Xi R41

Acute Tox. 4 H302, STOT RE 2 H373,
Eye Dam. 1 H318, Skin Irrit. 2 H315

EC. 203-868-0

INDEX. 603-071-00-1

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet. T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

SECTION 4 - FIRST AIDS MEASURES**4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists,

seek medical advice SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again. INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorized by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5 - FIREFIGHTING MEASURES**5.1. Extinguishing media.**

SUITABLE EXTINGUISHING EQUIPMENT Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapors and protect those trying to stem the leak. UNSUITABLE EXTINGUISHING EQUIPMENT Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6 - ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard. Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7 - HANDLING AND STORAGE**7.1. Precautions for safe handling.**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1. Control parameters.**

Regulatory References:

United Kingdom limits for use amended).	EH40/2005 Workplace exposure limits. Containing the list of workplace exposure with the Control of Substances Hazardous to Health Regulations (as
Éire OEL EU 2000/39/EC. TLV-ACGIH	Code of Practice Chemical Agent Regulations 2011. Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive ACGIH 2012

DIETHANOLAMINE**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
OEL	IRL	1			
TLV-ACGIH		1			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitril or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves` limit depends on the duration of exposure.

EYE PROTECTION Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an AX or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141). The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited. If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	white/ Colour
Odour	odourless
Odour threshold.	Not available.
pH.	\plain
Melting point / freezing point.	Not available.
Initial boiling point.	> 60 °C.
Boiling range.	Not available.
Flash point.	> 23 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,89 Kg/l
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	> 340 °C.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

VOC (Directive 1999/13/EC) : 2,25 % - 20,00 g/litre. VOC (volatile carbon) : 0

SECTION 10 - STABILITY AND REACTIVITY**10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11 - TOXICOLOGICAL INFORMATION

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This product may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

11.1. Information on toxicological effects.

DIETHANOLAMINE

LD50 (Oral). 710 mg/kg Rat LD50 (Dermal). 12200 mg/kg Rabbit

SECTION 12 - ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13 - DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Avoid littering. Do not contaminate soil, sewers and waterways. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14 - TRANSPORT INFORMATION

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

SECTION 15 - REGULATORY INFORMATION

TSCA: The components of this mixture are listed or are exempt from listing in the Toxic Substance Control Act Inventory of Chemical Substances. This product does not contain any chemicals that would require export notification under Section 12(b) of the TSCA regulation. This product contains no: Cadmium (Cd), Chromium (Cr), Lead (Pb), Tin (Sn), nor any organic elements that can cause cancer.

This product contains no ozone-depleting compounds

SECTION 16 - OTHER INFORMATION**Text of hazard (H) indications mentioned in section 2-3 of the sheet:**

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10	FLAMMABLE.
R22	HARMFUL IF SWALLOWED.
R36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
R38	IRRITATING TO SKIN.
R41	RISK OF SERIOUS DAMAGE TO EYES.
R48/22 EXPOSURE IF	HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED SWALLOWED.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. The Merck Index. - 10th Edition
9. Handling Chemical Safety
10. Niosh - Registry of Toxic Effects of Chemical Substances
11. INRS - Fiche Toxicologique (toxicological sheet)
12. Patty - Industrial Hygiene and Toxicology
13. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
14. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 11 / 15.