



# TECHNICAL DATA SHEET


















**VELLWAX**  
METALLIC WAX

**355ml**

## PRODUCT DESCRIPTION

MacoAve VELLWAX is a Water based metallic paste wax for decorating, protecting, sealing and polishing a wide variety of surfaces including, venetian plaster and marmorino plaster surfaces.

## PRODUCT & CODE

COLOR	UPC	COLOR	UPC
<b>W001</b> Translucent Purple	 9551003920952	<b>W009</b> K Gold	 9551003921034
<b>W002</b> Translucent Blue	 9551003920969	<b>W010</b> Copper Gold	 9551003921041
<b>W003</b> Translucent Silver	 9551003920976	<b>W011</b> Emerald Green	 9551003921058
<b>W004</b> Translucent Green	 9551003920983	<b>W012</b> Rose Gold	 9551003921065
<b>W005</b> Translucent Red	 9551003920990	<b>W013</b> Navy Blue	 9551003921072
<b>W006</b> Lemon Gold	 9551003921003	<b>W014</b> Dark Grey	 9551003921089
<b>W007</b> Plum Purple	 9551003921010	<b>W015</b> Ruby Red	 9551003921096
<b>W008</b> Tuscany Gold	 9551003921027		

## SURFACE PREPARATION

Surfaces to be finished must be clean, dry and free of wax, grease, scaling paint and mildew.

## PAINTING CONDITIONS

The wax is formulated for trowel, brush, sponge or cloth application. After removal of fat, oil and dust, once the surface is dry proceed with wax application, taking care to even with a cotton cloth. Apply whether possible in areas with temperatures not lower than 10/15 °C, with an humidity rate not higher than 70%. The lower the temperature and the higher the humidity, the longer will be the drying time of the product.

## COVERAGE

12 fl oz covers approximately 80-100 square feet. Depending on surface porosity and texture.

## PRODUCT APPLICATION

Can be apply with soft cloth, sponges or trowel, rub off excess wax. Initially applies to an opaque finish, but can be buffed with soft cloth to increase the sheen. Buff off access wax with cloth or polish machine. Two tone metallic wax can be apply to plaster wall to achieve multicolor design. Apply Macoavell Vellwax clear wax after 24 hours to seal and protect.

**PHYSICAL PROPERTIES**

Appearance	Paste
Colour	Clear / Coloured
Odour	Slightly perfumed
Density	0,89 g/cm <sup>3</sup>
Dry Residual	30%+/- 1% weight
Drying time (20°C)	20 minutes before polishing. After 1 hour dry to touch.
Viscosity	800 mPas(23° C)
Yield	30/40 gr/m <sup>2</sup>

**PACKAGING SIZE**

12 FL OZ. (355ml) covers approximately 80-100 square feet.  
Depending on surface porosity and texture.

**STORAGE**

Store in a cool, well ventilated place, keep the container close when not in use. Keep away from heat, flames, sparks and other sources of ignition. Shelf life of the product is 12 months.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.